

SCANNER BARCODE CS2600 SERIES



THE READER ULTIMATE BARCODE

GENERATION



HIGH PERFORMANCE 1D / 2D IMAGING TECHNOLOGY FOR THE MANAGEMENT OF INTENSIVE READING LOADS EVEN FROM THE SCREEN OF COMMON SMARTPHONES.

High performance and effective reading depth on different types of media, including smartphone and tablet screens. The new generation CMOS image sensor and the smart pointer system allow accurate reading even in the presence of small or damaged codes.

The special serial cable (optional) allows the direct power supply of the Axon Microlec range Telematics Loggers (Helios Series, Edo Plus Series, Aura Series), ensuring maximum reading compatibility and the correct acquisition of bar codes for the Lottery of Receipts, without the need for configuration. Also available in a kit version with an ergonomic desk stand for hands-free reading.

BARCODE



lottery receipt code
1D codes

QR CODE



2D codes

LCD FRIENDLY



readability from
the screen

PROTECTION



1.5m drop test



IP52

GENERAL CHARACTERISTICS

| | |
|--------------------------|--|
| • version of the scanner | corded manual |
| • CPUs | 32-bit ARM |
| • write yes Scan | Image |
| • Resolution | 1280 x 800 pixels |
| • Light source | Illumination: 5000K, white LED, maximum wavelength 525nm, tolerance to movement, minimum 5 IPS |
| • Angle of scanning | Horizontal 41°; Vertical 28° |
| • Sensitivity to read | Pitch $\pm 75^\circ$; Tilt 360°; Skew $\pm 70^\circ$ |
| • Trigger mode | Automatic or Manual |
| • firmware Upgrade | On-line |
| • Print Contrast | Min 20% |
| • Resolution minimum | HD: 1D code 39: 3mil SR: 1D code 39: 4mil |
| • Resolution maximum | 3mil Code39 (3 chars): 25–50mm 4mil Code39 (3 chars): 10–90mm 13mil UPC (6 chars): 0–250mm 20mil Code39 (1 char): 15–340mm 6.7mil PDF417 (20 chars): 10mm– 100mm 10mil QR (20 chars): 0–155mm 20mil QR (20 chars): 0–270mm |

SUPPORTED BARCODES

| | |
|----------------------------|---|
| • codes of code of bars 1D | Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand etc. |
| • codes of code of 2D bars | PDF417, QR Code, Data Matrix, HanXin, Maxicode, Postal Codes etc. |

INDICATORS

| | |
|--------------------|-------------------|
| • Indicator | bright LEDs |
| • Operations Sound | Notification beep |

INTERFACES AND POWER SUPPLY

| | |
|-----------|--|
| • Doors | Serial RS-232, USB keyboard, USB Virtual COM |
| • Voltage | 5VDC +/-10% |

PHYSICAL CHARACTERISTICS

| | |
|-----------------|-------------------------------|
| • Dimensions | 90 x 62.8 x 153mm (D x L x H) |
| • Weight | 132g (without cable) |
| • Certification | CE,FCC,RoHS |

OPERATING CONDITIONS

| | |
|-------------------------|--|
| • Temperature | Operation/ 0°C ~ +50°C Storage/ -40°C~ +60°C |
| • Humidity | 5% ~ 95% non-condensing |
| • brightness of reading | 100,000 LUX |
| • Endurance to falls | 2m drop test |
| • IP51 drop test | |

OPTIONS AND ACCESSORIES

| | |
|-----------------------|--|
| • lottery kit | RS-232 serial cable certified for receipt lottery, dedicated to Helios, Edo Plus and Aura series |
| • wires of Connection | 2 m standard USB cable 2 m standard RS-232 cable |
| • Source of feeding | 5V |

I left and registered appartengono a AP.esse spa o ai rispettivi proprietari. The images and the information on their products are not vincolanti and possibly they are soggette to modify senza obbligo di preavviso.