






MAIN FEATURES

- FULL HD 10" Display (1920 x 1200)
- Sunlight Readable
- Shock & Drop-Proof
- Dust & Water-Proof (IP65)
- CPU Intel Quad Core up to 1,92GHz
- Modem 4G (LTE) + GPS
- Barcode Reader (Opcional)
- 8 Hours Battery Life



SYSTEM

CPU	Intel CherryTrail Atom X5-Z8350 Quad Core 1,44Ghz up to 1,92GHz
MEMORY	4GB RAM
STORAGE	64GB eMMC
OPERATING SYSTEM	Windows 10 Pro

IN / OUT

WIFI / BLUETOOTH / GNSS / LTE	802.11 Dual a/b/g/n/AC Bluetooth 4.0 Dedicated GPS (Ublox) 4G Modem
PORTS	1 x Micro-USB 2.0 1 x USB 2.0 1 x Mini HDMI 1 x Audio 1 x SIM Slot 1 x Micro-SD (up to 128GB) 1 x DC-Jack 1 x Kensington 1 x Docking Connector
SOUND	Built-in Speaker and Microphone

DISPLAY

SIZE	LCD 8" IPS
BRIGHTNESS	750 Nits
RESOLUTION	1920 x 1200
BACKLIGHT	LED
TOUCHSCREEN TECHNOLOGY	Projected Capacitive (PCAP) Multi-Touch (10 points) Digitizer

ENVIRONMENT

OPERATING TEMPERATURE	-20°C ~ 60°C
HUMIDITY	5% - 95%

DURABILITY

DUST-PROOF WATER-PROOF	IP65 Total
SHOCK-PROOF DROP-PROOF	MIL-STD 810G
CHASSIS	Internal Aluminum Structure

WEIGHT & DIMENSIONS

WEIGHT	725 g
DIMENSIONS	228 x 145 x 17 mm

INCLUDES

CAMERAS	Front 2 Mp + charge LED Rear 5 Mp Autofocus + Flash
BUTTONS	Volume (+ / -), Power and Barcode Scan Trigger
SENSORS	Gyroscope G-Sensor
ADAPTERS	USB to Micro-USB 15cm and 1m Charger 220VAC 3-1 (EU-UK-US)
HAND STRAP	4 attachment points

OPTIONALS

VEHICLE POWER ADAPTER	12/24VDC to 5VDC DC-Jack
PASSIVE STYLUS	For Capacitive Touchscreen Tether
ACTIVE STYLUS	For Capacitive Touchscreen Tether 2 buttons
MULTIFUNCTION HAND STRAP	Shoulder / Neck Strap Hand Strap Desk Stand Leg / Vehicle Seat Strap S shaped Carabiner
DESKTOP DOCKING	Port Replicator: 3 x USB 2.0 / 1 x RJ45 1 x DC-Jack
CORPORATE WALL / VEHICLE SUPPORT	Montaje VESA 75/100 Bloqueo mediante llave
PREMIUM WALL / VEHICLE SUPPORT	VESA 75/100 Mount Key Lock Port Replicator: 2 x USB 2.0 / 1 x RS-232 1 x RJ45 / 1 x DC-Jack
BARCODE READER	NewLand N1 USB 1D & 2D

POWER SUPPLY

BATTERY	8h Autonomy 7.550mAh 27,9Wh 3,7VDC
POWER ADAPTER	In: 100-240VAC, 50-60 Hz Out: 5VDC 3A Charge: DC-Jack

OPTIONAL CONFIGURATION

C1820A2KCCDR-2DJT - [Barcode Reader]