

i.safe MOBILE

ZONE 2/22



4G telephony



High-performance battery for long work shifts



Amplified loudspeaker

IS360.2

The handy mobile phone is designed for the classic main functions of telephony and messaging (SMS). The IS360.2 is equipped with a proprietary operating system without Play Store. Customized applications can be installed by i.safe MOBILE. The simple operation via the 3" (7.62 cm) touchscreen and the convenient shape of the IS360.2 allow safe handling even in rough working environments. Thanks to the powerful battery, it is ideally suited for long working shifts. The amplified loudspeaker guarantees good audio quality even in noisy work environments and thus the best communication between interlocutors.

› All trademarks and copyrights are the properties of their respective owners. › © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1057MD01REV02_EN_04.2022



i.safe MOBILE

< IS360.2 >



ATEX approval: EX-Zone 2/22
Ⓜ II 3G Ex ic IIC T4 Gc
Ⓜ II 3D Ex ic IIC T135°C Dc



IECEx approval: EX-Zone 2/22
Ex ic IIC T4 Gc
Ex ic IIC T135°C Dc

TECHNICAL FEATURES

Operating system	Proprietary
Processor	MTK6739V Quad-core
Memory	1 GB RAM 8 GB internal memory
Frequencies	2G GSM: B2/3/5/8 3G WCDMA: B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/20/28
Dimensions	size: 118 x 58 x 25,8 mm weight: 197 g
Display	3" sunlight readable 480 x 854 pixels
Battery	3000 mAh replaceable
Camera	2 MP FF rear camera with LED flash light
Connections	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n Bluetooth® 4.2
Types of protection	IP68 dust-/waterproof MIL-STD-810H usable from -10 °C to +50 °C

FURTHER FEATURES



Accelerometer, proximity/light, magnetic sensors



freely programmable key

SET CONTENT

Smartphone, Battery, Belt Clip, Type C USB Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.