# Epson TM-L90 Series



The TM-L90 is Epson's compact thermal label printer that's also ideal for barcode printing. This model effortlessly increases productivity for post offices, pharmacies, supermarkets and other businesses. You can easily print on different types of label and receipt paper, in a variety of different sizes, thanks to the adjustable cutter.

## Label and barcode printing

With fast, thermal printing of up to 150mm/sec, the TM-L90 is a valuable asset to your business. With this model, you'll be able to print out and get on with more important work, rather than waiting around for labels or barcodes.

## More connectivity

This printer benefits from high speed serial, Ethernet and parallel connectivity plus a built-in USB interface, which means it can be operated as a network device.

## Easy to use

The small footprint and wall bracket mean that you can place it almost anywhere, in any position, for convenient and versatile printing. Practical design features, such as drop-in paper load, selectable auto-cutter and jamproof paper feeding, ensure smooth operation. The easy-to-use operator cover and lifespan of up to 20 million lines enable long-lasting, trouble-free maintenance.

## High quality labels

Its greyscale capabilities allow highly customised layouts, and logos and promotional messages can be added with ease.

## Larger receipt rolls, wider paper

Altogether, the TM-L90 label printer is one of the most efficient label printers available: it accepts large paper rolls (up to 90mm in diameter) and you can select paper widths between 38 and 80mm to produce labels in different sizes.

## DATASHEET



# **KEY FEATURES**

#### Versatile

Ideal for label and barcode printing. Supports greyscale printing.

- Fast print speeds Thermal printing up to 150mm/sec
- Easy installation Mounts horizontally, vertically or with a wall bracket

# Easy operation

Drop in paper loading and built-in-USB interface

Media flexibility

Label and receipt paper, from 38mm to 80mm wide



# PRODUCT SPECIFICATIONS

Print speed	150 mm/sec	
FONTS & STYLES		
Print Speed (label)	150 mm/sec	
Print Speed receipt	150 mm/sec	
Print Speed	150 mm/sec	
Character size	1.5 mm (W) x 3 mm (H) / 1.1 mm (W) x 2.1 mm (H)	
Character set	95 Alphanumeric, 18 set International, 128 x 7 Graphic	
Characters per inch	22.6 cpi / 16.9 cpi	
Dot density	203 dpi x 203 dpi	
Printing Characters	Barcode	
INTERFACES		
Interfaces	USB 2.0 Type B, Parallel (optional), RS-232 (optional), Ethernet interface (100 Base-TX / 10	
	Base-T) (optional)	
POWER		
Power Supply	PS-180	
Power Consumption	Mean: 1.8 A	
Operatingvoltage	24 V	
GENERAL		
Product dimensions	140 x 148 x 203 mm (Width x Depth x Height)	
Product weight	1.9 kg	
Colour	Epson Dark Gray / Epson Cool White	
Installation	horizontally, vertically with wall hanging bracket	
Interface connectors	D.K.D. function (2 drivers)	
DATA BUFFER		
Data Buffer	4 kB or 45 Bytes	
STANDARDS COMPLIANCE		
EMC Standards	VCCI class A, FCC class A, CE marking, AS / NZS 3548	
Safety standards	UL, CSA, TÜV	
OTHER FEATURES		
Changeable interface	Yes	
Cutter	Full Cut	
Sensors	Paper End Sensor, Paper Near End Sensor, Cover Open Sensor	
OTHER		
Warranty	24 months Carry in	
•		

# LOGISTICS INFORMATION

Dimensions Single Carton	257 x 193 x 241 mm
Carton Weight	2.5 Kg
Multiple Order Quantity	4 Units
Pallet Size Euro	168 Units (24 x 7)

Epson TM-L90 Series

# WHAT'S IN THE BOX

- Label paper roll
- Main unit
- PS-180
- Paper exit guide
- Paper roll spacer
- Power switch cover
- User manual
- Panel label for horizontal installation

# **OPTIONAL ACCESSORIES**

• WH-10 (040) Wall hanging bracket C32C845040

## EPSON<sup>®</sup> CoverPlus

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate. Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

