



TECH TO INDUSTRY

# PANEL PC Serie **SEYPOS KPS INOX**



Full  
IP65



FANLESS



M12



## LA TECNOLOGÍA AL ALCANCE DE TU MANO.



Stainless Steel Housing



Full IP65 and Optical bonding



M12

### Características principales

- Conexiones M12
- Full IP65
- Carcasa INOX
- P-CAP o resistiva
- Válvula de aire, antiempañamiento, con película interna de Gore-tex
- Optical bonding: sellado anti-humedad / entrada de líquidos / antirreflejo. Más dureza y brillo
- 2 años de garantía

|               | Panel Size | Resolution | Aspect ratio |
|---------------|------------|------------|--------------|
| SEYPOS KPS156 | 15.6"      | 1920x1080  | 16:9         |
| SEYPOS KPS185 | 18.5"      | 1366x768   | 16:9         |
| SEYPOS KPS215 | 21.5"      | 1920x1080  | 16:9         |
| SEYPOS KPS15  | 15"        | 1024x768   | 4:3          |
| SEYPOS KPS17  | 17"        | 1280x1024  | 4:3          |
| SEYPOS KPS19  | 19"        | 1280x1024  | 4:3          |
| SEYPOS KPS24  | 23.8"      | 1920x1080  | 16:9         |

## Especificaciones

### Main System

|                     |  |
|---------------------|--|
| CPU                 | Intel® Celeron J4125 2.0GHz , quad core,fanless                        |
| Memory              | 8GB  |
| Hard Drive Capacity | 128G SSD   |
| Graphics            | CPU Integrated graphics HD Graphics and support 1080p HD photo quality |
| Audio               | Realtek ALC662, High Definition Audio (HD), Line in, Line out          |
| Network             | 1xRealtek RTL 8111E Gigabit Ethernet controller                        |
| I/O Interface       | 3xUSB, 1xLAN, 1xRS232, 1xDCIN  |
| Operation System    | Support Windows 7/8/10, Linux, Ubuntu, Debian                          |

### LCD Panel

|                                 |                           |
|---------------------------------|---------------------------|
| Support color                   | 16.7M colors              |
| Brightness (cd/m <sup>2</sup> ) | 400 nits                  |
| Response time                   | 5ms                       |
| Contrast ratio                  | 1000:1                    |
| View angle                      | 80°/80°/80°/80° (R/L/U/D) |

### Touch Panel

|                     |  |
|---------------------|--|
| Touchscreen         | P-Cap Multi-touch / 5W resistive touch |
| Touch Interface     | USB                                    |
| Touch response time | 2ms                                    |
| Luminousness        | 90%                                    |
| Working Life        | >50 million times                      |

### Power Supply

|                       |                                      |
|-----------------------|--------------------------------------|
| External Power Supply | AC 100 - 240V                        |
| Working voltage       | DC 12V (9-36V wide voltage optional) |
| Power consumption     | ≤45W                                 |

### Enclosure

|               |                              |
|---------------|------------------------------|
| Material      | Stainless Steel SUS304L      |
| VESA mounting | 75x75mm/100x100mm            |
| IP Grade      | Full IP65 Water & Dust Proof |

### Operating Enviroment

|                   |   |
|-------------------|---|
| Temperature       | operating: -10 to 60°C, storage :-20 to 80°C                            |
| Relative humidity | 5%~95% @ 40° C, non-condensing  |
| Vibration         | 5-500 Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |

### Garantía

|          |        |
|----------|--------|
| Garantía | 2 años |
|----------|--------|

### Optional

|                    |  |
|--------------------|--|
| WIFI Optional      |  |
| Android            |  |
| i5 / i7            |  |
| High Brightness    |  |
| Vandal Proof Glass |  |