

sewoo

Desktop Label Printer

LK-B30II



- Fast Print Speed : 6 ips
- Excellent Compatibility
- Easy to use and maintenance
- Support label design software "Label Cooker"
- Compact design and advanced performance



WiFi



Bluetooth



Barcode



Durable



Wireless
Connectivity



Easy
Loading



Fast
Speed



Compact
Design



Easy
Replacement

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Thermal transfer and Direct thermal

Print Speed
Up to 6ips(152mm/sec)

Print Width
Up to 4.1”(104mm)

Resolution
203 dpi (8dots/mm)

Memory
1MB Main Flash, 16 SDRAM,
8MB Font flash

Sensor
Gap, Black mark, Cover open

Power
Type : External SMPS
AC : 100~240Vac, 1.5A, 50/60Hz
DC : 24Vdc/1.75A



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
7.48” x 10” x 4.29”
(190 x 254 x 169 mm)

Weight (Kg)
4.4lb(2kg)



MEDIA CHARACTERISTICS

Media Type
Roll, Fanfold, Blackmark,
Continuous, Gap, Notch Sensor

Media Width
0.8”~4.4”(22 ~ 114mm)

Media Roll Diameter
Internal : Ø 25.4(1”) or
Ø 38.1mm(1.5”)
Roll Diameter Max : Ø 5”(127mm)

Thickness
0.065~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 104°F(0 ~ 40°C)

Operating Humidity
10 ~ 90%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%



BARCODES

1D
Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128,
Code93, Codabar, Interleaved 2
of 5, UPC-A, UPC-E, UPC-A and E
with 2 or 5 digit extension, EAN-8,
EAN-13, EAN-8 and 13 with 2 or 5
digit extensions, Postnet, Plessey,
MSI-3, German Post CodeLogmars,
Code11, UPC_Interleaved 2 of 5,
Industrial 2 of 5, Standard 2 of 5,
Planet, ANSI, Logmars

2D
MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations
EPL II, ZPL II Command compatible

Drivers
Windows Driver
Linux Driver
Mac Driver

SDKs
Windows SDK
Android SDK
iOS SDK



INTERFACES

Standard
USB, Serial(RS-232C), Ethernet

Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KC, CE



FONTS / GRAPHICS

EPL II
6 bitmapped
8x12, 10x16, 12x20, 14x24,
32x48, 24x24(KSC5601)

ZPL II
9 bitmapped
5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24
2 smooth scalable(English, Korean)



ACCESSORIES

Standard
Power Cord, Power Supply,
Interface Cable(USB)

Optional
External Paper Supply

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

