



## PLUS4

### 4" Panel printer

PLUS4 allows you to print on 112mm large paper 4". The internal adjustable guides allow you to manage also paper sizes of 80 mm and 82.5mm in width. PLUS4 features exclusive characteristics in its class: it is equipped with an internal Flash Memory that will allow you to store characters and logos up to 4MB! Available on-board are Euro, International, Portuguese, Nordic, Chinese(GB18030) and Cyrillic characters. It can print the most common barcodes and 2D barcode, like QR CODE. The semi-transparent cover protects the paper sensor from the external light and allows you to view the paper and check for low paper. The paper compartment can be easily opened using the central green button. A module with serial and parallel interface is available as optional.



## CHARACTERISTICS

- Printing width: 104mm max
- It prints on linerless Maxstick B paper
- 4MB internal flash memory for logos and fonts
- Barcodes: 1D/ 2D (QR CODE)
- Characters: European, International, Portuguese and Nordic, Chinese (GB18030) and Cyrillic
- Status LED
- FEED button
- ECO mode: low power consumption during printing
- Metal tear-off
- Interface: RS232/TTL (selectable with lever switch), mini USB
- Sensors: head temperature, paper presence, door open (optional)
- Conform to UL, CE, FCC, CCC
- Power supply 5-8Vdc
- Management of AV05 rewinder

## APPLICATIONS:

- Healthcare: sterilization and electrocardiographs
- Vacuum packaging machines
- Temperature control: industrial refrigeration
- Industrial automation: process control
- Sales attempt
- Weighing instruments, physical and electric quantity analysis instruments

## SOFTWARE:



**CePrinterSet SOFTWARE** : to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.



With a unique printer's model it is possible to print both on standard thermal paper and on "linerless" adhesive paper Maxstick B, being then able to satisfy different needs and applications.

## AVAILABLE VERSIONS:

- RS232/TTL and mini USB, 5-8Vdc
  - Mechanical version (without electronic board)
- 

## ACCESSORIES



- RS232 serial module (DB9) USB (standard) Centronics (25 pin) input 9-40Vdc

## What is in the box:

- Device, paper adjustment guides, fixing hooks
-

## TECHNICAL SHEET

<b>Printing Method</b>	Thermal
Number of dots	8 dots/mm
Columns	46 (11cpi) 59 (15cpi) 83 (20cpi)
Resolution	204 DPI
Printing (mm/sec)	min 50, max 70 mm/sec
Character set	European, International, Portuguese and Nordic, Chinese (GB18030) and Cyrillic
Supported Barcode	1D, 2D and QRCODE
Paper width	112 mm (max 114mm) with internal guides for 80 and 82.5mm formats
Paper weight	60 g/m <sup>2</sup>
Printing width	max 104mm
Roll Dimension	External diameter: 50mm max 50mm Internal diameter: 104 mm max
Sensors	head temperature, paper end, cover open (optional)
Emulation	Escape Command, PlusII compatibility
Interfaces	RS232/TTL, mini USB,
Data Buffer	2 kB
Flash Memory	4 MB
Graphic Memory	1 MB internal flash memory + 4MB external flash memory; 128 KB internal RAM + 8MB external RAM
Drivers	Windows Linux
Software Tools	CePrinterSet
Power supply	5-8 Vdc
Operating temperature	-10 to +60
Marks	UL, CE, FCC, CCC
Dimensions	149(L) X 97.8(H) x 71.7(W) mm 89.1(W) mm with module
Weight	390gr (510gr with module)

## MODELS



### 915GJ010100322

PRINTER 112MM PLUS4 USB RS232

TTL



CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: TI80WI0

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 11 December 2020

