

RUGGED TABLET RT 309





The Rugged Tablet PC, in pocket-size, built for fieldwork in the most challenging outdoor or industrial environments.



Windows 10 Pro/IoT
Intel Quad-Core
Display 8.1 inch 1920 x 1200
4GB Ram, 64GB Storage
NFC front reading
Wireless, Bluetooth, 4G LTE

www.ruggtek.com



Operating System Computing Platform Computing Platform System Memory Storage Graphic Display Storage Graphic Intel HD Graphics Intel HD Gr	Model	RT 309		
Intel Atom x5-28350			Windows 10 IoT Enterprise on request *	
System Memory Storage 646B SSD Graphic Intel HD Graphics Display 8.1 inch 1920 x 1200 2/2 resolution display, 16:10 Touchscreen Ethernet Gigabit Ethernet 1000Mbit/s Bluetooth Wireless IEEE 802.11a/b/g/nac compatible Ceditular network Location Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Audio Audio Aomo Speaker and Headphone Camera Keyboard Interfaces 1958 2.0 R145 ethernet port * DB 9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card S				
Storage 646B SSD Intel HD Graphics Dual Display support			4 Cores, up to 1.726 nz	
Intel HD Graphics Dual Display support				
Display Resolution IPS technology (and Sunshine readable *) 1920 x 1200 2K resolution display, 16:10 Portrait or Landscape, automatic screen rotation Portrait or Landscape, automatic screen rotation User selectable by finger, pen and glove Ethernet Gigabit Ethernet 1000Mbit/s Bluetooth 4.2 wireless technology IEEE 802:11a/b/g/n/ac compatible 2.4GHz and 5.0GHz, Dual Band support Cellular network Location Sult-in GPS, GLONASS, BeiDou A-GPS support A-GPS	_		Dood Disasters and	
Touchscreen	-	·		
Touchscreen Capacitive multi-touch Ethernet Gigabit Ethernet 1000Mbit/s Bluetooth Bluetooth Bluetooth Wireless Bluetooth 4.2 wireless technology Wireless Celtular network Location Sensors Audio Mono Speaker and Headphone Camera Keyboard Power button, Volume up/down, Barcode scanner (and 2 programmable buttons *) USB 3.0 USB 2.0 USB 2.0 RJ45 ethernet port * DBy serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Built-in RFC reader UHF RFID *** External GNSS connector High precision GPS Security Falls and South Action Built-in rechargeable lithium-ion battery Falls as prover, 780 Built-in Parles design - No fan. No noise, Drop Resistance Drop Resistance Use Size Action Use Resistance Use Size Action User selectable by finger, pen and glove 2.4GHz and 5.0GHz, Dual Band support Actor Data A-GPS support Actor Data A-GPS support AutoFocus rear camera AutoFocus				
Touchscreen Ethernet Bluetooth Bluetooth A 2 wireless technology Wireless IEEE 802.11a/b/g/n/ac compatible Cellular network Location Built-in GPS, GLONASS, BeiDou A-GPS support Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Audio Audio Mono Speaker and Headphone Camera Keyboard Interfaces Wiss 3.0 USB 2.0 RJ45 ethernet port * USB 2.0 RJ45 ethernet port ethernet port ethernet port port port port port port port por	Resolution	1920 x 1200		
Bluetooth Bluetooth Bluetooth Bluetooth Bluetooth A.2 wireless technology				
Bluetooth Wireless IEEE 802.11a/b/g/n/ac compatible 2.4GHz and 5.0GHz, Dual Band support		•	User selectable by finger, pen and glove	
Vireless IEEE 802.11a/b/g/n/ac compatible 2.4GHz and 5.0GHz, Dual Band support	Ethernet			
Cellular network Location Built-in GPS, GLONASS, BeiDou A-GPS support A-GPS support Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Audio Mono Speaker and Headphone Camera Keyboard Interfaces WSB 3.0 USB 2.0 R145 ethernet port * DB9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Built-in Barcode reader Built-in Freeder UHF RFID Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader* Power Built-in Freedaredrafter AC/DC Power Adapter Cooling System Dimensions Weight Environment ** Expansion Slots Built resistance Dust Resistance Dust Resistance Dust Resistance Dust Resistance Dust Resistance Drop Resistance Dust Resistance Adulfor sensor, Magnetometer, Proximity sensor A-GPS support A-GPS support Adulfor Support A-GPS support Adulfor sensor, Magnetometer, Proximity sensor Adulfor sensor, Magnetometer, Proximity sensor Adulfor support adventers, Magnetometer, Proximity sensor Adulfor Support A-GPS suppo	Bluetooth			
Location Built-in GPS, GLONASS, BeiDou A-GPS support	Wireless	IEEE 802.11a/b/g/n/ac compatible	2.4GHz and 5.0GHz, Dual Band support	
Ambient Light sensor, 3-axis Motion sensor, Magnetometer, Proximity sensor Audio Audio Amono Speaker and Headphone Camera Keyboard Interfaces USB 3.0 USB 2.0 R145 ethernet port * DB9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Built-in Barcode reader UHF RFID *** External GNSS connector High precision GPS Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Weight Environment ** Environment ** Mono Speaker and Headphone 2 Muto Focus and Headphone 2 Muto Focus and Hauto Focus and Hauto-Cambala Surface Auto-Couling System Dimensions Weight Environment ** AutoFocus rear camera	Cellular network	4G LTE	Data	
Audio Camera ZMP front, SMP rear AutoFocus rear camera AutoFocus rear camera Reyboard Interfaces USB 3.0 USB 2.0 RJ45 ethernet port * DB9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Built-in NFC reader UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * Power AC/DC Power Adapter Dimensions Width 23 4mm, Height 144mm, Depth 17mm Weight Environment ** Environment ** Expension Came Dust Resistance UPF Resistance Dust Resistance UPF Resistance UPF Resistance UPF Resistance UPF Resistance UPF Resistance UPF Resistance AutoFocus rear camera Auto	Location	Built-in GPS, GLONASS, BeiDou	A-GPS support	
Camera Keyboard Power button, Volume up/down, Barcode scanner (and 2 programmable buttons *) USB 3.0	Sensors	· · · · · · · · · · · · · · · · · · ·		
New Power button, Volume up/down, Barcode scanner (and 2 programmable buttons *) Interfaces USB 3.0	Audio			
New Power button, Volume up/down, Barcode scanner (and 2 programmable buttons *) Interfaces USB 3.0	Camera		AutoFocus rear camera	
Interfaces USB 3.0 USB 2.0 RJ45 ethernet port * DB9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Expansion Slots * Built-in Barcode reader Built-in NFC reader UHF RFID *** External GNSS connector High precision GPS Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Glass protection Drop Resistance Drop Resistance Drop Resistance Drop Resistance Drop Resistance UP6x x1 L1 L2 L1	Kevboard		(and 2 programmable buttons *)	
USB 2.0 RJ 45 ethernet port * DB9 serial RS-232 * HDMI Micro SD Memory Card Slot SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Built-in Barcode reader Built-in NFC reader UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * David Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** DIMP Resistance DIMP Resistance Dire Resistance Dire Resistance Dire Resistance Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Place 122m Dire Resistance IP6x	-			
RJ45 ethernet port * x1 DB9 serial RS-232 * x1 HDMI x1 Micro SD Memory Card Slot x1 SIM Card x1 3.5mm Headphone jack x1 Charging - DC In power jack x1 Docking connector x1 Built-in NFC reader 1D and 2D barcode support Built-in NFC reader 13.56MHz, front reading UHF RFID *** External GNSS connector High precision GPS Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselle AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection Prop Resistance Dust Resistance IP6x	interraces		, ,	
DB9 serial RS-232 * X1 HDMI X1 Micro SD Memory Card Slot X1 SIM Card X1 3.5mm Headphone jack X1 Charging - DC In power jack X1 Docking connector X1 Expansion Slots * Built-in Barcode reader ID and 2D barcode support Built-in NFC reader I3.56MHz, front reading UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselled AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection Prop Resistance IP6x				
HDMI x1 Micro SD Memory Card Slot x1 SIM Card x1 3.5mm Headphone jack x1 Charging - DC In power jack x1 Docking connector x1 Expansion Slots * Built-in Barcode reader Built-in NFC reader UHF RFID *** External GNSS connector Instead of Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection Selection Selection Input: 122m Dust Resistance IP6x				
Micro SD Memory Card Slot x1 SIM Card x1 3.5mm Headphone jack x1 Docking connector x1 Built-in Barcode reader 1D and 2D barcode support Built-in NFC reader 13.56MHz, front reading UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection Prop Resistance Dust Resistance IP6x				
SIM Card 3.5mm Headphone jack Charging - DC In power jack Docking connector Expansion Slots * Built-in Barcode reader Built-in NFC reader UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * Power Built-in rechargeable lithium-ion battery Cooling System Dimensions Weight Environment ** Glass protection Drop Resistance Dust Resistance SIM Card X1				
3.5mm Headphone jack x1 Charging - DC In power jack x1 Docking connector x1 Built-in Barcode reader ID and 2D barcode support Built-in NFC reader I3.56MHz, front reading UHF RFID *** External 6NSS connector High precision 6PS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection Prop Resistance Dust Resistance IP6x				
Charging - DC In power jack x1 Docking connector x1 Expansion Slots * Built-in Barcode reader 1D and 2D barcode support Built-in NFC reader 13.56MHz, front reading UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselled AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance IP6x				
Docking connector x1 Expansion Slots * Built-in Barcode reader Built-in NFC reader Built-in Fire Built-in Fire Built-in Fire Built-in Fingerprint reader * Built-in Fingerprint reader * Built-in Fingerprint reader * Built-in rechargeable lithium-ion battery Built-in Fingerprint Fire Built-in F		·		
Expansion Slots * Built-in Barcode reader 1D and 2D barcode support Built-in NFC reader 13.56MHz, front reading UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm 424 approx.700g Environment ** Glass protection 58H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance 1P6x				
Built-in NFC reader UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery 7800mAh Replaceable battery by Ruggtek authorised reselled have been been been been been been been be				
UHF RFID *** External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter AC/DC Power Adapter Cooling System Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Glass protection Drop Resistance Dust Resistance Dust Resistance Dust Resistance Drop Resistance Dust Resistance Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A **BH anti-scratch and anti-shock surface Drop Resistance Drop Resistance Drop Resistance Dust Resistance Drop Resistance	Expansion Slots *			
External GNSS connector High precision GPS Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Cooling System Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Glass protection Drop Resistance Dust Resistance Dust Resistance Dust Resistance Dust Resistance Dust Resistance Differ Store Light Store Up to 5 fingerprints stored PR00mAh Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Replaceable battery by Ruggtek authorised reselled Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Security Batter			13.56MHz, front reading	
High precision GPS Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * up to 5 fingerprints stored Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Cooling System Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Glass protection Drop Resistance Dust Resistance Dust Resistance Trusted Platform Module (TPM) 2.0 up to 5 fingerprints stored Up to 5 fingerprints stored Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Panless design - No fan. No noise. Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Panless design - No fan. No noise. Panl		UHF RFID ***		
Security Trusted Platform Module (TPM) 2.0 Built-in Fingerprint reader * Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Cooling System Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Glass protection Drop Resistance Dust Resistance Dust Resistance Drop Resistance		External GNSS connector		
Built-in Fingerprint reader * up to 5 fingerprints stored Built-in rechargeable lithium-ion battery AC/DC Power Adapter Cooling System Dimensions Weight Environment ** Glass protection Drop Resistance Dust Resistance Built-in Fingerprint reader * up to 5 fingerprints stored 7800mAh Replaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Replaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Ruggtek authorised reselle Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Seplaceable battery by Rugg		High precision GPS		
Power Built-in rechargeable lithium-ion battery AC/DC Power Adapter Cooling System Dimensions Weight Environment ** Built-in rechargeable lithium-ion battery AC/DC Power Adapter Fanless design - No fan. No noise. Width 234mm, Height 144mm, Depth 17mm approx.700g Environment ** Glass protection Drop Resistance Dust Resistance Dust Resistance Drop Resistance	Security	Trusted Platform Module (TPM) 2.0		
Replaceable battery by Ruggtek authorised reselled AC/DC Power Adapter Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance Dust Resistance IP6x		Built-in Fingerprint reader *	up to 5 fingerprints stored	
Replaceable battery by Ruggtek authorised reselled AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance Dust Resistance IP6x	Power	Built-in rechargeable lithium-ion battery	7800mAh	
AC/DC Power Adapter Input: 100-240VAC, 50/60Hz, Output: 5VDC, 3A Cooling System Fanless design - No fan. No noise. Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance IP6x		, , , , , , , , , , , , , , , , , , ,	Replaceable battery by Ruggtek authorised reseller	
Cooling System Dimensions Width 234mm, Height 144mm, Depth 17mm Weight Environment ** Or Resistance Dust Resistance Fanless design - No fan. No noise. Width 234mm, Height 144mm, Depth 17mm approx.700g **8H anti-scratch and anti-shock surface 1.22m Dust Resistance IP6x		AC/DC Power Adapter		
Dimensions Width 234mm, Height 144mm, Depth 17mm Weight approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance IP6x	Cooling System		, , , , , , , , , , , , , , , , , , ,	
Weight approx.700g Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance IP6x				
Environment ** Glass protection >8H anti-scratch and anti-shock surface Drop Resistance 1.22m Dust Resistance IP6x		, , , ,		
Drop Resistance 1.22m Dust Resistance IP6x			>8H anti-scratch and anti-shock surface	
Dust Resistance IP6x				
		·		
water Resistance IPX5				
Operating Temperature -10 °C to 50 °C				
Humidity 0% to 90% relative humidity, non-condensing		· · · · · · · · · · · · · · · · · · ·		
Vibration & Shock In accordance with MIL-STD-810G			In accordance with MIL-STD-810G	
Regulatory CE, MIL-STD-810G, WEEE, RoHS				
Ordering Code RT 309, 4GB RAM, 64GB SSD, OS Windows	Ordering Code			
Included in the box Hand holder, Power Adapter, Cables, Quick User Guide, Warranty document	Included in the box	· · · · · · · · · · · · · · · · · · ·		
Accessories * User replaceable anti-glare screen protector, Capacitive Pen with soft rubber,	Accessories *	User replaceable anti-glare screen protector, Capacitive Pen with soft rubber,		
Office Docking with Battery Charger, Rugged Docking for wall-mount,				
Vehicle Docking, combinations RAM and VESA holder, Power Adapter for Vehicle,				
Shoulder strap, Bluetooth Keyboard, Special cable for RJ45 port, Special cable for RS-232 port.		-		

www.ruggtek.com

^{*} Optional

^{**} Tested by an independent third-party lab following CE, MIL-STD-810G and IEC 60529.

^{***} Non-Standard Part, assembly by request. A minimum order quantity (MOQ) is required.